

MTB

Modell	model	SQUAD 3.0 MTB BOOST
Design	design	MATT WHITE
Carbonfaser	carbon fiber	3K-Carbon
Abmaße Felge	dimension rim	622 x 30,5 Hookless tubeless ready
Reifendimension	tyres	clincher 54-62mm
Reifendruck (max.)	tyre inflation pressure	3,5 bar (29x2,10 Zoll) /52 psi in (54-622) 3,2 bar (29x2,20 Zoll) /46 psi in (57-622) 2,9 bar (29x2,35 Zoll) /41 psi in (60-622) 2,6 bar (29x2,50 Zoll) /37 psi in (62-622)
Bremsfläche	brake surface	none
Bremsbeläge	brake pads	none
Gesamtgewicht [g]	total weight [g]	1644
max. empfohlenes Fahrergewicht inkl. Ausrüstung [kg]	max. recommended rider weight incl. Equipment [kg]	110
Zubehör	accessories	XeNTIS warranty card XeNTIS wheelbag XeNTIS rim tape

Vorderrad	front wheel	
Felgenhöhe [mm]	rim depth [mm]	30-ASYMMETRIC PROFILE
Felgenbreite [mm]	rim width [mm]	36
Tachomagnet	speedometer magnet	-
Vorderrad Nabe	front hub	XeNTIS XH002-BO, 15-100mm, 6-hole IS 2000
Einbaubreite Nabe [mm]	built in width hub [mm]	110
Speichenanzahl	spokes count	28
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge rechts [mm]	spoke length right [mm]	298
Speichenlänge links [mm]	spoke length left [mm]	298
Dekor	decor	white
Oberfläche (UV Schutz)	surface (UV protection)	matt
empfohlene Ventillänge [mm]	recommended valve length [mm]	40
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	-

Hinterrad	rear wheel	
Felgenhöhe [mm]	rim depth [mm]	30-ASYMMETRIC PROFILE
Felgenbreite [mm]	rim width [mm]	36
Tachomagnet	speedometer magnet	-
Hinterrad Nabe	rear hub	XeNTIS XH002-BO, X12-142mm, 6-hole IS 2000
Kompatibilität 1	compatibility 1	Shimano / SRAM 10/11-Speed
Kompatibilität 2	compatibility 2	Shimano Micro Spline 12s
Kompatibilität 3	compatibility 3	SRAM XDR 12-Speed
Einbaubreite Nabe	built in width hub [mm]	148
Speichenanzahl	spokes count	28
Speichen	spoke	Sapim CX-Ray SP
Speichennippel System	spoke-nipple system	DT Squorx
Speichenlänge rechts [mm]	spoke length right [mm]	298
Speichenlänge links [mm]	spoke length left [mm]	298
Dekor	decor	white
Oberfläche (UV Schutz)	surface (UV protection)	matt
empfohlene Ventillänge [mm]	recommended valve length [mm]	40
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	-

Item Number		Description
18S30MTBBO29440-S	1pair	Wheelset, QR15-110 / X12-148 BOOST, SRAM/Shimano 10/11s
18MS30MTBBO29440-S	1pair	Wheelset, QR15-110 / X12-148 BOOST, Shimano Micro Spline 12s
18X30MTBBO29440-S	1pair	Wheelset, QR15-110 / X12-148 BOOST, SRAM XDR 12s
18S30MTBBO29440-R	1pcs	Rear wheel, X12-148 BOOST, SRAM/Shimano 10/11s
18MS30MTBBO29440-R	1pcs	Rear wheel, X12-148 BOOST, Shimano Micro Spline 12s
18X30MTBBO29440-R	1pcs	Rear wheel, X12-148 BOOST, SRAM XDR 12s
18S30MTBBO29440-F	1pcs	Front wheel, QR15-110 BOOST
18S30MTBLE29440-F	1pcs	Front wheel, Lefty SM 2.0 / OCHO

XeNTIS Produkte können Abweichungen enthalten, Spezifikationen können ohne vorherige Ankündigungen geändert werden.
Gewichtsschwankungen (+/- 5%) können aufgrund der Produktionsmethode des Laufrades auftreten. Irrtümer und Änderungen vorbehalten!

XeNTIS products may not be exactly as shown, specifications subject to change without notice.
Weight tolerances (+/- 5%) may occur due to the manufacturing process. Errors and omissions excepted!