

**MTB**

Modell	model	<b>KAPPA 2 27.5</b>
Design	design	<b>MATT WHITE</b>
Carbonfaser	carbon fiber	<b>12K-Carbon</b>
Abmaße Felge	dimension rim	<b>584 x 25C tubeless ready</b>
Reifendimension	tyres	<b>clincher 47-60mm</b>
Reifendruck (max.)	tyre inflation pressure	<b>3,5 bar (27,5x1,85 Zoll) /50 psi in (47-584) 3,0 bar (27,5x2,10 Zoll) /43 psi in (54-584) 2,7 bar (27,5x2,25 Zoll) /37 psi in (57-584) 2,4 bar (27,5x2,35 Zoll) /34 psi in (60-584)</b>
Bremsfläche	brake surface	<b>none</b>
Bremsbeläge	brake pads	<b>none</b>
Gesamtgewicht [g]	total weight [g]	<b>1384</b>
max. empfohlenes Fahrergewicht inkl. Ausrüstung [kg]	max. recommended rider weight incl. Equipment [kg]	<b>120</b>
Zubehör	accessories	<b>XeNTiS warranty card XeNTiS wheelbag XeNTiS rim tape</b>

<b>Vorderrad</b>	<b>front wheel</b>	
Felgenhöhe [mm]	rim depth [mm]	<b>35</b>
Felgenbreite [mm]	rim width [mm]	<b>30,2</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Vorderrad Nabe	front hub	<b>XeNTiS XH002, 15-100mm, 6-hole IS 2000</b>
Einbaubreite Nabe [mm]	built in width hub [mm]	<b>100</b>
Speichenanzahl	spokes count	<b>4</b>
Speichen	spoke	<b>-</b>
Speichennippel System	spoke-nipple system	<b>-</b>
Speichenlänge [mm]	spoke length [mm]	<b>-</b>
Dekor	decor	<b>white</b>
Oberfläche (UV Schutz)	surface (UV protection)	<b>matt</b>
empfohlene Ventillänge [mm]	recommended valve length [mm]	<b>40</b>
Gewicht Schnellspanner Vorderrad [g]	weight quick release front wheel [g]	<b>-</b>

<b>Hinterrad</b>	<b>rear wheel</b>	
Felgenhöhe [mm]	rim depth [mm]	<b>35</b>
Felgenbreite [mm]	rim width [mm]	<b>30,2</b>
Tachomagnet	speedometer magnet	<b>✓</b>
Hinterrad Nabe	rear hub	<b>XeNTiS XH004, X12-142mm, 6-hole IS 2000</b>
Kompatibilität 1	compatibility 1	<b>Shimano / SRAM 10/11-Speed</b>
Kompatibilität 2	compatibility 2	<b>Shimano Micro Spline 12s</b>
Kompatibilität 3	compatibility 3	<b>SRAM XDR 12-Speed</b>
Einbaubreite Nabe	built in width hub [mm]	<b>142</b>
Speichenanzahl	spokes count	<b>4</b>
Speichen	spoke	<b>-</b>
Speichennippel System	spoke-nipple system	<b>-</b>
Speichenlänge rechts [mm]	spoke length right [mm]	<b>-</b>
Speichenlänge links [mm]	spoke length left [mm]	<b>-</b>
Dekor	decor	<b>white</b>
Oberfläche (UV Schutz)	surface (UV protection)	<b>matt</b>
empfohlene Ventillänge [mm]	recommended valve length [mm]	<b>40</b>
Gewicht Schnellspanner Hinterrad [g]	weight quick release rear wheel [g]	<b>-</b>

Item Number		Description
18SKAP527450-S	1pair	Wheelset, QR5-100 / QR5-135, SRAM/Shimano 10/11s
18MSKAP527450-S	1pair	Wheelset, QR5-100 / QR5-135, Shimano Micro Spline 12s
18XKAP527450-S	1pair	Wheelset, QR5-100 / QR5-135, SRAM XDR 12s
18SKAP1527450-S	1pair	Wheelset, QR15-100 / X12-142, SRAM/Shimano 10/11s
18MSKAP1527450-S	1pair	Wheelset, QR15-100 / X12-142, Shimano Micro Spline 12s
18XKAP1527450-S	1pair	Wheelset, QR15-100 / X12-142, SRAM XDR 12s
18SKAP527450-R	1pcs	Rear wheel, QR5-135, SRAM/Shimano 10/11s
18MSKAP527450-R	1pcs	Rear wheel, QR5-135, Shimano Micro Spline 12s
18XKAP527450-R	1pcs	Rear wheel, QR5-135, SRAM XDR 12s
18SKAP1527450-R	1pcs	Rear wheel, X12-142, SRAM/Shimano 10/11s
18MSKAP1527450-R	1pcs	Rear wheel, X12-142, Shimano Micro Spline 12s
18XKAP1527450-R	1pcs	Rear wheel, X12-142, SRAM XDR 12s
18SKAP527450-F	1pcs	Front wheel, QR5-100
18SKAP1527450-F	1pcs	Front wheel, QR15-100

XeNTiS Produkte können Abweichungen enthalten, Spezifikationen können ohne vorherige Ankündigungen geändert werden.  
Gewichtsschwankungen (+/- 5%) können aufgrund der Produktionsmethode des Laufrades auftreten. Irrtümer und Änderungen vorbehalten!

XeNTiS products may not be exactly as shown, specifications subject to change without notice.  
Weight tolerances (+/- 5%) may occur due to the manufacturing process. Errors and omissions excepted!